

# Product information



## DeavX

The DeavX filter module is an independently operating filter and can easily be used as a gatekeeper in a small-scale pipeline network, a pipe section or an individual tapping point. The filter is suitable for cold water installations with a maximum temperature of 40 °C | 104 °F.

With the periodic forward flush, pollution is automatically flushed away. The automatic flushing of the filter combined with annual maintenance results in a lifespan of 5 years.

The DeavX has minimal management costs, annual thorough cleaning of the modules and settings check is sufficient.

# Details

## Included in product:

- Solenoid and timer
- Three way couplings
- Manual valves
- Manometers
- Mesh prefilter
- Check valve
- Filter clamps
- Power cord 2m | 78"

Art. nr.	Description	Capacity*		HxWxD (cm)
1119090350	DeavX 1	0,5 m3/h	2.2 GPM	79×32×15
1119090510	DeavX 2	0.75 m3/h	3.3 GPM	96×32×15
1119090750	DeavX 3	1.1 m3/h	4.4 GPM	116×32×15
1119110750	DeavX 4	1 m3/h	4.4 GPM	123×35×16
1119125750	DeavX 5	2 m3/h	8.8 GPM	124×36×17
1119160750	DeavX 6	3.5 m3/h	15.5 GPM	127×38×20
1119160100	DeavX 7	5 m3/h	22 GPM	156×38×20

\* At clean water flux 16°C / 60°F | 2 bar / 29 PSI.

- Long-term solution against legionella
- Plug-and-play delivered
- Applications: shower, legionella prevention, pre filtration reverse osmose, restaurants
- Ask for the full additional options list
- Ask for technical datasheet

